

## DEPARTMENT OF ADMINISTRATION

DIPATTAMENTON ATMENESTRASION

**GENERAL SERVICES AGENCY** 

(Ahensian Setbision Hinirat)
Telephone (Telifon): (671) 475-1707/1729 • Fax (Faks): (671) 472-4217/1727



September 21, 2020

## **INVITATION FOR BID**

## GSA-014-20 ELECTRIC REACH TRUCK/FORKLIFT

## **AMENDMENT #3**

- 1. Amend to change "Bid Opening" date from: September 22, 2020 at 9:00am To now read: September 28, 2020 at 11:00 am.
- 2. Amend to replace page 35 of 38 with the "Revised 9-21-20" page 35 of 38 (Attached) All others remain unchanged.

CLAUDIA S. ACFALLE Chief Produrement Officer

Please Print ACKNOWLEDGEM	ENT COPY (Re-fax to GSA)
Received By:	
Date:	
Company Name:	
Fa	ax to: 475-1727 or 472-4217
E-mail to: gs	aprocurement@gsadoa.guam.gov

SPECIFICATIONS:	BIDDING ON/REMARKS
Electrical System: The successful bidder shall provide <u>Multi-Voltage Battery Charger</u> that is compatible with the existing <u>building</u> power. Charger shall <u>be compatible with the battery supplied and shall be</u> installed by the successful bidder before or at the time of delivery.	
Charger shall have the following rating: AC INPUT 208/240/480 Volts 40/36/18 AMPS 60 HERTZ 1 PHASE MAX OUTPUT 36 VOLTS/136 AMPS.	
Building Power is three (3) phase <u>208 VAC</u> , However, Charging area in warehouse has a single-phase panel, 208 VAC protected by a 50 Amp breaker.	
If charger to be supplied requires a power supply other than the existing power supply the bidder shall be responsible for all cost associated with the conversion, to include but not limited to materials/hardware, labor etc.	-
Battery shall be 36 V with a charge capacity that allows for at least 8 Hours of operation between charging periods. Battery storage system Shall include any available standard or optional features to allow for Easy removal and replacement.	s
Operator's Station: Standard stand up type. Standard operator controls and overhead guard Conforms to all current industry standards. To include all manufacture's standard features as stated in brochure.	
Steering: Electric/Power, with manufacturer's standard fixed or adjustable Steering control position.	
Tires/Wheels: Standard size with rubber drive wheel option if available.	
Color: Manufacturer's standard color	
Safety Equipment: 2 inch reflective tape strips shall be installed on the back and side of lift truck also on the mast and load backrest to increase visibility of forklift while in operation.	
Required Lighting:  Manufacturer's standard or optional – work lights front & rear.  Mounted to allow maximum visibility shall be provided.	
Safety Equipment: Equipment shall meet all applicable OSHA regulations. All safety, instruction, and warning labels shall be in English.	
Additional Options:  Backup alarm and electric horn  Strobe, amber beacon light, flush mounted or magnetic.  Counter weights: Manufacturer's recommended amount if required.  Lift and Tilt locking control valve.	
<b>Note:</b> The unit shall be delivered completely assembled, serviced, and ready to operate. The bidder shall have a qualified service representative in attendance with the equipment during the delivery start-up operations to make any adjustments needed and to give operator/s instruction on the proper operation.	

Please Print	
ACKNOWLEDGEMENT COPY (Re-fax to G	SSA)
Received By:	•
Date:	
Company Name:	

"Revised 9-21-20" Page **35** of **38**